

MHF308 (3 RF Rotary joints + Electric)

MMHF308 is 3 channel RF Rotary joints mixed with electric wires, max 72 wires, are standard, ready available slip ring solution.

Use gold contacts at the rotary interface for signal rings, and 3 channel RF Rotary joints for large amount data transmitting.

can combine with Large current, Thermocouples, Ethernet, USB on request.



Specifications

PART #	HANNEL	FREQUENCY	2A/SIGNAL	10A	CONNECTORS
MHF308-06S	3	DC-1.5GHz	6	0	SMA
MHF308-0610	3	DC-1.5GHz	0	6	SMA
MHF308-12S	3	DC-1.5GHz	12	0	SMA
MHF308-1210	3	DC-1.5GHz	0	12	SMA
MHF308-0610-06S	3	DC-1.5GHz	6	6	SMA
MHF308-18S	3	DC-1.5GHz	18	0	SMA
MHF308-1810	3	DC-1.5GHz	0	18	SMA
MHF308-24S	3	DC-1.5GHz	24	0	SMA

Electric Specifications

Rating voltage	2 10 VDC / 240 VAC	Contact material	Precious Metal:Gold-Gold
Dielectric strength	600VDC@50Hz	Lead Wire	UL Teflon®
Insulation resistance	1000MΩ@500VDC	Lead Lengths	250mm
Operating Temp	-40°C to 80°C	Protection	IP51
Mechanical vibratio	MIL-SID-810E	Humidity	10% to 90% RH
Materials	Lead Free,RoHS compliant	CE Certified	YES

(RF Rotary joints) Specifications

Max speed	20RPM	Torque	1N.m
Frequency	0-1.5Ghz	Insertion loss	0.3dB
Insertion loss ripple	0.05dB	VSWR	≤1.3
VSWR ripple	0.05	Start up torque	0.1N.m
Estimated life cycle	100 million	Housing materia	Stainless steel
Working temperature	-40 to 85 °C	Storage temperature	-50 to 85 °C
IP rating	IP 68	Weight	50g

Drawings

12 wires for one group color. from 13 ... 24, repeat the same color as 1 ... 12, indicated with number code pipe.

Lead wire Color codes

Rings#	Color Code	Rings#	Color Code	Rings#	Color Code
1	BLK	5	YEL	9	GRY
2	BRN	6	GRN	10	WHT
3	RED	7	BLU	11	PINK
4	ORN	8	PURPLE	12	AZURY

Options

- Optional flange mounting.
- Specified the wire exit direction.
- Can combine more electric wires:1-72Ring
- Specified connectors and Heat-shrink tube.
- Longer lead lengths available.
- Shielded cables
- Connectors
- Environmentally Sealed up to IP68@4Mpa
- Frequencies up to 500 MHz
- High-speed data transmission for fast Ethernet and EtherCat
- Signal, Coax, and Power combinations
- High Speed up to 20,000 rpm
- Thermocouples
- Shock, Vibration, and Temperature Qualified
- Pneumatic/Hydraulic Capability
- High temperature---up to 450 degree
- High Voltage & large Current(1000A)
- IP65,IP68 are avialable.
- Military Grade.

Build on Request


Build On Your Request/Special requirements

when we can't find any one of standard part# to fit our application, what should we do?

Great! Moflon supply build-on-request service base on MHF308 series, the delivery time of build-on-request is 2~3 weeks, and price is only 20%~50% more than the standard version.

Now, Let's start - how to build on request?

Please see ordering information instructions as below:



For example:

if order MHF308 with 3wires*15A each + 12wires*signal, the model should be **MHF308-0315-12S**.

if order MHF308 with 12wires*signal + 3wires*80A, the model should be **MHF308-0380-12S**

Please note: MHF308 could combine with Ethernet, Coaxial(RF), USB, and so on.

if you have other optional requirements, such as lead wire length, connectors, military grade, Please describe in your email.

After Finishing above, pls send email to us: technical@moflon.com for further technical support.